



NVIDIA Quadro NVS 290

## Raising the Bar for Professional 2D Graphics

NVIDIA Quadro® NVS 290 graphics board brings a new level of performance, quality and stability for professional 2D multi-display environments.

Ground-breaking NVIDIA® unified architecture dynamically allocates geometry, shader, and compute processing power to efficiently deliver optimized performance. Featuring 256MB frame buffer and two single-link DVI-I connectors, NVIDIA Quadro NVS 290 offers the industry's best image quality at resolutions up to 1920 x 1200 @ 60Hz.

The NVIDIA Quadro NVS 290 is the professional 2D solution from a wide

range of product offerings. The entire NVIDIA Quadro family takes the leading computer-aided design (CAD), digital content creation (DCC), and visualization applications to a new level of interactivity by enabling unprecedented capabilities in programmability and precision. The industry's leading workstation applications leverage this architecture to enable hardware-accelerated features not found in any other professional graphics solution. Featuring

NVIDIA Quadro FX 5600, 5500, and 4500 X2 at the ultra-high-end, NVIDIA Quadro FX 4600 and 3500 at the high-end, NVIDIA Quadro FX 3450 and 1700 at the mid-range, NVIDIA Quadro FX 570 and 370 at the entry-level, and NVIDIA Quadro NVS 440, NVS 290, NVS 285, NVS 280 at the professional 2D segment, NVIDIA Quadro delivers unmatched workstation performance and quality.

### Product Specifications

Form Factor	Low Profile, 2.731" (H) x 6.6" (L)
Frame Buffer Memory	256MB DDR2
Memory Interface	64-bit
Memory Bandwidth	6.4GB/sec.
Max Power Consumption	21W
Graphics Bus	PCI Express x16 and x1
Display Connectors	DMS-59
Single Link DVI	Yes (2)
Auxiliary Power Connectors	No
Number of Slots	1
Thermal Solution	Passive heatsink





# NVIDIA Quadro | The Standard for Multi-Display Business Graphics.

## Features and Benefits

<b>NVIDIA Unified Architecture</b>	Industry's first unified architecture designed to dynamically allocate GPU resources to deliver optimized performance.
<b>Essential for Microsoft® Windows Vista™</b>	Offering an enriched 3D user interface, increased application performance, and the highest image quality, NVIDIA Quadro graphics boards and NVIDIA OpenGL ICD drivers are optimized for 32- and 64-bit architectures to enable the Windows Vista experience.
<b>256MB DDR2 Frame Buffer Memory</b>	Delivers high throughput for interactive visualization of large models and high-performance for real time processing of large textures and frames and enables the highest quality and resolution full-scene antialiasing (FSAA).
<b>Low-Profile Form Factor</b>	Enables support for small form factor systems.
<b>nView Multi-Display Technology<sup>1</sup></b>	The NVIDIA nView hardware and software technology combination delivers maximum flexibility for multi-display options, and provides unprecedented end-user control of the desktop experience.
<b>NVIDIA PureVideo™ Technology</b>	NVIDIA PureVideo technology is the combination of high-definition video processors and software that delivers unprecedented picture clarity, smooth video, accurate color, and precise image scaling for SD and HD video content. Features include, high-quality scaling, spatial temporal de-interlacing, inverse telecine, and high quality HD video playback from DVD.
<b>GPU Computing</b>	NVIDIA CUDA™ provides a C language environment and tool suite that unleashes new capabilities to solve complex, visualization challenges such as real-time ray tracing and interactive volume rendering.
<b>High Performance Display Outputs</b>	400MHz RAMDACs and two DVI-I connectors drive both analog and digital displays, with single-link TMDS transmitters supporting high-resolution digital panels (up to 1920 x 1200 @ 60Hz) — which result in amazing image quality producing detailed photorealistic images.
<b>Ultimate Image Quality</b>	Quadro NVS graphics products deliver the industry's best image quality, sharpness and pixel tracking for analog LCDs, DLPs and plasma displays with resolutions up to 2048 x 1536 at 85Hz.
<b>Fanless Design</b>	With a passive heatsink, accoustics is not a problem to achieve a quieter desktop environment.
<b>Unified Driver Architecture<sup>2</sup></b>	The NVIDIA UDA guarantees forward and backward compatibility with software drivers. Simplifies upgrading to a new NVIDIA product because all NVIDIA products work with the same driver software.

## Product Specifications

### SUPPORTED PLATFORMS

- Microsoft Windows Vista (64-bit and 32-bit)
- Microsoft Windows® XP (64-bit and 32-bit)
- Microsoft Windows 2000 (32-bit)
- Linux® - Full OpenGL® implementation, complete with NVIDIA and ARB extensions (64-bit and 32-bit)
- Solaris®
- AMD64, Intel EM64T

### NVIDIA QUADRO FX 290 ARCHITECTURE

- 128-bit color precision
- Unlimited fragment instruction
- Unlimited vertex instruction
- 3D volumetric texture support
- 12 pixels per clock rendering engine
- 3rd-generation occlusion culling
- 16 textures per pixel in fragment programs
- Window ID clipping functionality
- Hardware accelerated line stippling

### DISPLAY RESOLUTION SUPPORT

- Two single-link DVI-I outputs drive digital displays at resolutions up to 1920 x 1200 @ 60Hz
- Internal 400 MHz DACs – Two analog displays up to 2048 x 1536 @ 85Hz



<sup>1</sup> NVIDIA nView will be available for Windows Vista Spring 2008

<sup>2</sup> Quadro NV280 PCI is supported on a separate driver branch

To learn more about NVIDIA Quadro, go to [www.nvidia.com](http://www.nvidia.com)

